Printing date 06.02.2023 Version number 1 Revision: 06.02.2023 SECTION 1: Identification of the substance/mixture and of the company/undertaking * · 1.1 Product identifier · Trade name: Aerosol SOLL White Primer · (Article number) product ID.: S700006 · 1.2 Relevant identified uses of the substance or mixture and uses advised against • Sector of Use SU21 Consumer uses: Private households / general public / consumers · Application of the substance / the mixture: painting • Uses advised against No further relevant information available. \cdot 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: UAB "HELVINA" · Parko str. 96 · LT-54464 Ramučiai · Kaunas distr., Lithuania Tel: +370 37 308 901 Fax: +370 37 308 902 info@helvina.lt www.helvina.lt · Further information obtainable from: Product safety department • 1.4 Emergency telephone number: Tel: +370 5 236 2052 / +370 687 53378 · national: National Poisons Information Service, Birmingham Tel.: 844 892 0111 · K-Nr. 0015 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 flame H222 Extremely flammable aerosol. Aerosol 1 H229 Pressurised container: May burst if heated. Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. · Hazard pictograms GHS02 GHS07 · Signal word Danger (Contd. on page 2) GB

Printing date 06.02.2023

Version number 1

Revision: 06.02.2023

Trade name: Aerosol SOLL White Primer

	(Contd. of page 1)
Hazard-determ	ining components of labelling:
acetone	
n-butyl acetate	
Hazard stateme	ents
H222 Extremely	y flammable aerosol.
	ed container: May burst if heated.
H319 Causes se	prious eye irritation.
H336 May caus	e drowsiness or dizziness.
Precautionary s	statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.
P305+P351+P	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Additional info	rmation:
Without adequa	te ventilation, explosive atmosphere/gas mix may be created.
	rdous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
2.3 Other hazar	rds

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

*

· Description: Mixture of substances listed below with nonhazardous additions.

CAS: 67-64-1	acetone	25-<50%
EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	� Flam. Liq. 2, H225; � Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether Flam. Gas IA, H220; Press. Gas (Comp.), H280, EUH018	10-<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	10-<25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane (containing ≤ 0,1 % butadiene (203-450-8)) ♦ Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	5-<10%
		(Contd. on pag

Printing date 06.02.2023

Version number 1

Revision: 06.02.2023

Trade name: Aerosol SOLL White Primer

		(Contd. of page 2
CAS: 75-28-5	isobutane (containing $\leq 0,1$ % butadiene (203-450-8))	5-<10%
	Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	
Reg.nr.: no Reach No. availlable	nitrocellulose with water(not less than 25% water, by mass)	2.5-<5%
	ethanol 🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319	2.5-<5%
	n-butyl acetate 🚸 Flam. Liq. 3, H226; ᡧ STOT SE 3, H336, EUH066	2.5-<5%
EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene, mixture of isomers Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1-<2.5%
	butyl glycollate � Repr. 2, H361; � Eye Dam. 1, H318	<1%
	trizinc bis(orthophosphate) 🚯 Aquatic Acute 1, H410	<i>≥</i> 0.025-<0.25%

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media -
- · Suitable extinguishing agents: Cool container whit water
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13.

(Contd. on page 4)

GB

Printing date 06.02.2023

Version number 1

Revision: 06.02.2023

Trade name: Aerosol SOLL White Primer

(Contd. of page 3)

Ensure adequate ventilation. • **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace.

• Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:

· Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

106-97-8 butane (containing ≤0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

1330-20-7 xylene, mixture of isomers

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

(Contd. on page 5)

GB

Printing date 06.02.2023

Version number 1

Revision: 06.02.2023

Trade name: Aerosol SOLL White Primer

(Contd. of page 4)

 • Ingredients with biological limit values:

 1330-20-7 xylene, mixture of isomers

 BMGV
 650 mmol/mol creatinine

 Medium: urine

 Sampling time: post shift

 Parameter: methyl hippuric acid

 • Additional information: The lists valid during the making were used as basis.

 • 8.2 Exposure controls

 • Appropriate engineering controls No further data; see item 7.

 • Individual protection measures, such as personal protective equipment

- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.
- · Respiratory protection:

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

· Hand protection

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material
- Gloves must be changed after every contamination.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
- butyl rubber, 0,7mm • Eye/face protection
- Safety glasses



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- \cdot 9.1 Information on basic physical and chemical properties
- General Information
- · Physical state
- · Colour: · Odour:

Aerosol Different colour shades Solvent-like

(Contd. on page 6)

Printing date 06.02.2023

Version number 1

Revision: 06.02.2023

Trade name: Aerosol SOLL White Primer

	(Contd. of page)
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling	
range	-44.5 °C (74-98-6 propane)
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	1.5 Vol % (106-97-8 butane (containing $\leq 0,1$ %
	butadiene (203-450-8)))
Upper:	18.6 Vol % (115-10-6 dimethyl ether)
Flash point:	<0 °C
Ignition temperature:	235 °C (115-10-6 dimethyl ether)
Decomposition temperature:	Not determined.
рН	Not determined.
Viscosity:	Nor determined.
Kinematic viscosity	Not determined.
Dynamic:	Not determined.
Solubility	1101 aciel mineu.
soluolluy water:	Not miscible or difficult to mix
	Not miscible or difficult to mix. Not determined.
Partition coefficient n-octanol/water (log value)	
Vapour pressure at 20 °C:	3,600 hPa (74-98-6 propane)
Density and/or relative density	0775 / 3
Relative density	0.775 g/cm^3
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Aerosol
Important information on protection of health and	d
environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation o
	explosive air/vapour mixtures are possible.
	Not determined.
Solvent content:	
Organic solvents:	87.8 %
organic sorrenis.	With propellant gas. Content given by weight.
Water:	0.0 %
VOC (EU)	(<840g/l)
	87.76 %
Solida contenti	9.0 %
Solids content:	7.U 70
Change in condition	Not applicable
Evaporation rate	Not applicable.
Information with regard to physical hazard classe	S
Explosives	Void
Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised container
	May burst if heated.
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
•	Void
Pyrophoric liquids	V 17114
Pyrophoric liquids Pyrophoric solids	
Pyrophoric liquids Pyrophoric solids	Void

Printing date 06.02.2023

Version number 1

Revision: 06.02.2023

Trade name: Aerosol SOLL White Primer

		(Contd. of page 6
· Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit flamm	able	
gases in contact with water	Void	
Oxidising liquids	Void	
• Oxidising solids	Void	
Organic peroxides	Void	
• Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards

· Endocrine disrupting properties

556-67-2 octamethylcyclotetrasiloxane

SECTION 12: Ecological information

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Ikke relevant.

• 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 8)

List II. III

Printing date 06.02.2023

Version number 1

Revision: 06.02.2023

Trade name: Aerosol SOLL White Primer

(Contd. of page 7)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

 \cdot Recommendation

*

*

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR	1950 AEROSOLS
IMDG	AEROSOLS
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
Class	2.1 Gases.
Label	2.1
14.4 Packing group	
ADR, IMDG, IATA	Void
	not classified
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Gases.
Hazard identification number (Kemler code):	-
	not classified
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
	SW2 Clear of living quarters.

Version number 1 Revision: 06.02.2023 Printing date 06.02.2023 Trade name: Aerosol SOLL White Primer (Contd. of page 8) SG69 For AEROSOLS with a maximum capacity of 1 · Segregation Code litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · 14.7 Maritime transport in bulk according to IMO instruments Not applicable. • Transport/Additional information: · ADR · Limited quantities (LQ) lLCode: E0 • Excepted quantities (EQ) Not permitted as Excepted Quantity · Transport category 2 • Tunnel restriction code D · IMDG lL \cdot Limited quantities (LQ) Code: E0 · Excepted quantities (EQ) Not permitted as Excepted Quantity

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture VOC: <840g/l

UN 1950 AEROSOLS, 2.1

· Directive 2012/18/EU

· UN "Model Regulation":

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:

· Technical instructions (air):

Class	Share in %
NK	50-100

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H201 Explosive; mass explosion hazard.
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.

(Contd. on page 10)

GB

Printing date 06.02.2023

Version number 1

Revision: 06.02.2023

Trade name: Aerosol SOLL White Primer

	(Contd. of	nage 9)
H280	Contains gas under pressure; may explode if heated.	ru50))
H304	May be fatal if swallowed and enters airways.	
H312	Harmful in contact with skin.	
H315	Causes skin irritation.	
H318	Causes skin innanon. Causes serious eye damage.	
H318 H319		
	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H336	May cause drowsiness or dizziness.	
H361	Suspected of damaging fertility or the unborn child.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
EUH018	8 In use may form flammable/explosive vapour-air mixture.	
	6 Repeated exposure may cause skin dryness or cracking.	
	ment issuing SDS: Product safety department	
	iations and acronyms:	
	cord relatif au transport international des marchandises dangereuses par route (European Agreement Concern	ing the
	onal Carriage of Dangerous Goods by Road)	ing ine
	ternational Maritime Code for Dangerous Goods	
IATA: Inte	vernational Air Transport Association	
	obally Harmonised System of Classification and Labelling of Chemicals	
	European Inventory of Existing Commercial Chemical Substances	
	European List of Notified Chemical Substances	
	emical Abstracts Service (division of the American Chemical Society) sistent, Bioaccumulative and Toxic	
	ry Persistent and very Bioaccumulative	
	: Explosives – Division 1.1	
	s IA: Flammable gases – Category IA	
Aerosol 1:	: Aerosols – Category 1	
: Aerosols	s – Category 3	
	is (Comp.): Gases under pressure – Compressed gas	
	<i>q. 2: Flammable liquids – Category 2</i>	
	y. 3: Flammable liquids – Category 3	
	x. 4: Acute toxicity – Category 4 . 2: Skin corrosion/irritation – Category 2	
	. 1: Serious eye damage/eye irritation – Category 1	
-	2: Serious eye damage/eye irritation – Category 2	
	Reproductive toxicity – Category 2	
STOT SE 3	3: Specific target organ toxicity (single exposure) – Category 3	
	2: Specific target organ toxicity (repeated exposure) – Category 2	
	1: Aspiration hazard – Category 1	
	Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1	
Aquatic Ci	Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1	
• * Data C	compared to the previous version altered.	