Printing date 06.02.2023 Version number 1 Revision: 06.02.2023

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Aerosol SOLL Black Primer
- · (Article number) product ID.: S700007
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU21 Consumer uses: Private households / general public / consumers
- · Application of the substance / the mixture: painting
- · Uses advised against No further relevant information available.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

UAB "HELVINA"

- · Parko str. 96
- · LT-54464 Ramučiai
- · Kaunas distr., Lithuania

Tel: +370 37 308 901 Fax: +370 37 308 902 info@helvina.lt www.helvina.lt

- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: Tel: +370 5 236 2052 / +370 687 53378
- · national:

National Poisons Information Service, Birmingham

Tel.: 844 892 0111

· K-Nr. 0015

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1 H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02

GHS07

· Signal word Danger

(Contd. on page 2)

Printing date 06.02.2023 Version number 1 Revision: 06.02.2023

Trade name: Aerosol SOLL Black Primer

(Contd. of page 1)

#### · Hazard-determining components of labelling:

acetone

n-butyl acetate

#### · Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

*P211* Do not spray on an open flame or other ignition source.

*P251* Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell. P337+P313 If eye irritation persists: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · Additional information:

Without adequate ventilation, explosive atmosphere/gas mix may be created.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

#### · 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	acetone  Flam. Liq. 2, H225;  Eye Irrit. 2, H319; STOT SE 3, H336, FUH066	25-<50%
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether  Flam. Gas 1A, H220; Press. Gas (Comp.), H280,	10-<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	10-<25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane (containing ≤ 0,1 % butadiene (203-450-8))  Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate  Flam. Liq. 3, H226	5-<10%

(Contd. on page 3)

Printing date 06.02.2023 Version number 1 Revision: 06.02.2023

Trade name: Aerosol SOLL Black Primer

a.a. == 00 =		(Contd. of page 2
CAS: 75-28-5	isobutane (containing $\leq 0.1$ % butadiene (203-450-8))	<i>5-&lt;10%</i>
EINECS: 200-857-2	Flam. Gas 1A, H220; Press. Gas (Comp.), H280,	
Reg.nr.: 01-2119485395-27-xxxx	EUH018	
CAS: 9004-70-0	nitrocellulose with water(not less than 25% water, by	2.5-<5%
Reg.nr.: no Reach No. availlable	mass)	
	♦ Expl. 1.1, H201	
CAS: 64-17-5	ethanol	2.5-<5%
EINECS: 200-578-6	🔥 Flam. Liq. 2, H225; 🕦 Eye Irrit. 2, H319	
Reg.nr.: 01-2119457610-43-xxxx		
CAS: 123-86-4	n-butyl acetate	2.5-<5%
EINECS: 204-658-1	🏵 Flam. Liq. 3, H226; 🕚 STOT SE 3, H336, EUH066	
Reg.nr.: 01-2119485493-29-xxxx		
CAS: 1330-20-7	xylene, mixture of isomers	1-<2.5%
EINECS: 215-535-7	📀 Flam. Liq. 3, H226; 😵 STOT RE 2, H373; Asp. Tox.	
Reg.nr.: 01-2119488216-32-xxxx	1, H304; (1) Acute Tox. 4, H312; Acute Tox. 4, H332;	
	Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 7397-62-8	butyl glycollate	<1%
EINECS: 230-991-7	& Repr. 2, H361; 😂 Eye Dam. 1, H318	
Reg.nr.: 01-2119514685-36-xxxx		
CAS: 7779-90-0	trizinc bis(orthophosphate)	<i>≥</i> 0.025-<0.25%
EINECS: 231-944-3	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
Reg.nr.: 01-2119485044-40-xxxx		

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media -
- · Suitable extinguishing agents: Cool container whit water
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

(Contd. on page 4)

Printing date 06.02.2023 Version number 1 Revision: 06.02.2023

Trade name: Aerosol SOLL Black Primer

(Contd. of page 3)

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

### · 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with	limit values tha	t require moi	nitoring at the	workplace:
--------------------	------------------	---------------	-----------------	------------

#### 67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

### 115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

### 106-97-8 butane (containing $\leq 0.1 \%$ butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm

Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

#### 108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

#### 64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

#### 123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

#### 1330-20-7 xylene, mixture of isomers

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

(Contd. on page 5)

Printing date 06.02.2023 Version number 1 Revision: 06.02.2023

Trade name: Aerosol SOLL Black Primer

(Contd. of page 4)

#### · Ingredients with biological limit values:

#### 1330-20-7 xylene, mixture of isomers

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

#### · Hand protection

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

Gloves must be changed after every contamination.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

butyl rubber, 0,7mm

· Eye/face protection

Safety glasses



Tightly sealed goggles

### SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Physical state Aerosol

· Colour: Different colour shades

· Odour: Solvent-like

(Contd. on page 6)

Printing date 06.02.2023 Version number 1 Revision: 06.02.2023

Trade name: Aerosol SOLL Black Primer

(Contd. of page 5)

Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

 $\cdot \textit{Boiling point or initial boiling point and boiling}$ 

range

· Flammability Not applicable.

· Lower and upper explosion limit

• Lower: 1.5 Vol % (106-97-8 butane (containing  $\leq 0.1$  %

butadiene (203-450-8)))

-44.5 °C (74-98-6 propane)

• *Upper:* 18.6 Vol % (115-10-6 dimethyl ether)

· Flash point: <0 °C

• Ignition temperature: 235 °C (115-10-6 dimethyl ether)

Decomposition temperature: Not determined.
pH Not determined.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

· Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

• Vapour pressure at 20 °C: 3,600 hPa (74-98-6 propane)

· Density and/or relative density

Relative density
 Vapour density
 0.775 g/cm<sup>3</sup>
 Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health and

environment, and on safety.

• Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

Not determined.

· Solvent content:

• Organic solvents: 87.8 %

With propellant gas. Content given by weight.

• Water: 0.0 %
 • VOC (EU) (<840g/l)</li>
 • Solids content: 9.0 %

· Change in condition

• Evaporation rate Not applicable.

· Information with regard to physical hazard classes

· Explosives Void · Flammable gases Void

· Aerosols Extremely flammable aerosol. Pressurised container:

May burst if heated.

Oxidising gases
Gases under pressure
Flammable liquids
Flammable solids
Self-reactive substances and mixtures
Pyrophoric liquids
Pyrophoric solids

(Contd. on page 7)

Printing date 06.02.2023 Version number 1 Revision: 06.02.2023

Trade name: Aerosol SOLL Black Primer

		(Contd. of page 6)
· Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit flamma	ble	
gases in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards

· Endocrine disrupting properties	
556-67-2 octamethylcyclotetrasiloxane	List II, III

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Ikke relevant.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

GR

Printing date 06.02.2023 Version number 1 Revision: 06.02.2023

Trade name: Aerosol SOLL Black Primer

(Contd. of page 7)

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR · IMDG · IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
· ADR	
· Class	2 5F Gases.
· Label	2.1
· Class	2.1 Gases.
· Label	2.1
· 14.4 Packing group · ADR, IMDG, IATA	Void not classified
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Hazard identification number (Kemler code):	Warning: Gases. - not classified
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat.

(Contd. on page 9)

Printing date 06.02.2023 Version number 1 Revision: 06.02.2023

Trade name: Aerosol SOLL Black Primer

	(Contd. of page
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of litre:
	Segregation as for class 9. Stow "separated from" class except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2 For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2
· 14.7 Maritime transport in bulk accord	ding to IMO
instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0
1 1 ( 2)	Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities $(\widetilde{EQ})$	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

## **SECTION 15: Regulatory information**

- $\cdot$  15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture VOC: <840g/l
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	50-100

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Relevant phrases
- H201 Explosive; mass explosion hazard.
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.

(Contd. on page 10)

Printing date 06.02.2023 Version number 1 Revision: 06.02.2023

Trade name: Aerosol SOLL Black Primer

· \* Data compared to the previous version altered.

(Contd. of page 9) H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. EUH018 In use may form flammable/explosive vapour-air mixture. EUH066 Repeated exposure may cause skin dryness or cracking. · Department issuing SDS: Product safety department · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Expl. 1.1: Explosives - Division 1.1 Flam. Gas 1A: Flammable gases - Category 1A Aerosol 1: Aerosols - Category 1 : Aerosols - Category 3 Press. Gas (Comp.): Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Repr. 2: Reproductive toxicity - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

GB