

## Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name **SOLL ANTIGRAVEL Stone Chip, white (Art.no. S700301; S700308)**  
Chemical name and synonym **not applicable (mixture)**

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Protective coating for carbody; Sound-deadening coating.**

Identified Uses	Industrial	Professional	Consumer
PROFESSIONAL USE	-	✓	-
INDUSTRIAL USE	✓	-	-

#### 1.3. Details of the supplier of the safety data sheet

UAB "HELVINA"  
Parko str. 96  
LT-54464 Ramučiai  
Kaunas distr., Lithuania  
Tel: +370 37 308 901  
Fax: +370 37 308 902  
E-mail: info@helvina.lt  
www.helvina.lt

#### 1.4. Emergency telephone number

For urgent inquiries refer to: Tel: +370 5 236 2052 / +370 687 53378

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

##### Hazard classification and indication:

Flammable liquid, category 2	H225	Highly flammable liquid and vapour.
Specific target organ toxicity - repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



## SECTION 2. Hazards identification ... / >>

Signal words: Danger

Hazard statements:

**H225** Highly flammable liquid and vapour.  
**H373** May cause damage to organs through prolonged or repeated exposure.  
**H319** Causes serious eye irritation.  
**H315** Causes skin irritation.  
**H335** May cause respiratory irritation.  
**H412** Harmful to aquatic life with long lasting effects.

Precautionary statements:

**P210** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
**P260** Do not breathe dust / fume / gas / mist / vapours / spray.  
**P280** Wear protective gloves/ protective clothing / eye protection / face protection.  
**P370+P378** In case of fire: use carbon dioxide, foam, chemical powder to extinguish.  
**P233** Keep container tightly closed.  
**P312** Call a POISON CENTRE / doctor / . . . if you feel unwell.

**Contains:** REACTION MASS OF ETHYLBENZENE AND XYLENE

VOC (Directive 2004/42/EC) :

Special finishes.

VOC given in g/litre of product in a ready-to-use condition : 430,00

Limit value: 840,00

### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

## SECTION 3. Composition/information on ingredients

### 3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
<b>REACTION MASS OF ETHYLBENZENE AND XYLENE</b> <i>INDEX</i>	$20 \leq x < 25$	<b>Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C</b> <b>STA Dermal: 1100 mg/kg, STA Inhalation vapours: 11 mg/l</b>
<i>EC</i> 905-588-0 <i>CAS</i> <i>REACH Reg.</i> 01-2119488216-32-XXXX		
<b>HEPTANE</b> <i>INDEX</i>	$5 \leq x < 9$	<b>Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 2 H411, Classification note according to Annex VI to the CLP Regulation: C</b>
<i>EC</i> 927-510-4 <i>CAS</i> 64742-49-0 <i>REACH Reg.</i> 01-2119475515-33-XXXX		
<b>XYLENE (MIXTURE OF ISOMERS)</b> <i>INDEX</i>	$0 \leq x < 0,5$	<b>Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C</b> <b>STA Dermal: 1100 mg/kg, STA Inhalation vapours: 11 mg/l</b>
<i>EC</i> 215-535-7 <i>CAS</i> 1330-20-7 <i>REACH Reg.</i> 01-2119488216-32		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## SECTION 4. First aid measures

### 4.1. Description of first aid measures

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

**SKIN:** Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

**INHALATION:** Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

**INGESTION:** Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

## SECTION 5. Firefighting measures

### 5.1. Extinguishing media

#### SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

#### UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

### 5.2. Special hazards arising from the substance or mixture

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

### 5.3. Advice for firefighters

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point

## SECTION 6. Accidental release measures ... / >>

13.

### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage

### 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s)

Information not available

## SECTION 8. Exposure controls/personal protection

### 8.1. Control parameters

Regulatory References:

DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2022

## SECTION 8. Exposure controls/personal protection ... / >>

### XYLENE (MIXTURE OF ISOMERS)

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	440	100	880	200	SKIN
MAK	DEU	440	100	880	200	SKIN
VLA	ESP	221	50	442	100	SKIN
VLEP	FRA	221	50	442	100	SKIN
VLEP	ITA	221	50	442	100	SKIN
TGG	NLD	210		442		SKIN
VLE	PRT	221	50	442	100	SKIN
NDS/NDSch	POL	100		200		SKIN
TLV	ROU	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH			20			

### REACTION MASS OF ETHYLBENZENE AND XYLENE

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	440	100	880	200	SKIN
MAK	DEU	440	100	880	200	SKIN
VLA	ESP	221	50	442	100	SKIN
VLEP	FRA	221	50	442	100	SKIN
VLEP	ITA	221	50	442	100	SKIN
TGG	NLD	210		442		SKIN
VLE	PRT	221	50	442	100	SKIN
NDS/NDSch	POL	100		200		SKIN
TLV	ROU	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

#### Predicted no-effect concentration - PNEC

Normal value in fresh water	0,32	mg/l
Normal value in marine water	0,32	mg/l
Normal value for fresh water sediment	12,46	mg/kg
Normal value for marine water sediment	12,46	mg/kg
Normal value for marine water, intermittent release	12,46	mg/l
Normal value for the terrestrial compartment	2,31	mg/kg

#### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			12,5					
			mg/kg/d					
Inhalation			65,3		442		221	
			mg/m3		mg/kg		mg/m3	
Skin	125		125				212	
			mg/kg/d				mg/kg/d	

## SECTION 8. Exposure controls/personal protection ... / >>

### HEPTANE

#### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	
MAK	DEU	2100	500	2100	500	
VLA	ESP	2085	500			Como n-Eptano
VLEP	FRA	1668	400	2085	500	
VLEP	ITA	2085	500			
TGG	NLD	1200		1600		
VLE	PRT	2085	500			
NDS/NDSch	POL	1200		2000		
TLV	ROU	2085	500			
WEL	GBR	2085	500			
OEL	EU	2085	500			
TLV-ACGIH		1639	400	2049	500	

#### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			149 mg/kg bw/d					
Inhalation			447 mg/m <sup>3</sup>				2085 mg/m <sup>3</sup>	
Skin			149 mg/kg bw/d				300 mg/kg bw/d	

#### Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.  
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

#### HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

#### Hand protection :

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

-Polychloroprene (CR; >= 1 mm thickness) or natural rubber (NR; >=1 mm thickness) .

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

-Polychloroprene (CR; >= 1 mm thickness) or natural rubber (NR; >=1 mm thickness) or nitrile rubber (NBR; >=1 mm thickness).

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances.

Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature).

If signs of wear and tear are noticed then the gloves should be replaced.

## SECTION 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	grey, white	
Odour	characteristic of solvent	
Melting point / freezing point	not available	
Initial boiling point	> 70 °C	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	-1 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	not applicable	Reason for missing data:substance/mixture is non-soluble (in water)
Kinematic viscosity	28000	Method:cst Temperature: 25 °C
Dynamic viscosity	40000	Method:CPS (Brookfield RVT) Temperature: 25 °C
Solubility	insoluble in water	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	1,43	
Relative vapour density	not available	
Particle characteristics	not applicable	

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

Information not available

#### 9.2.2. Other safety characteristics

Total solids (250°C / 482°F)	71,00 %		
VOC (Directive 2004/42/EC) :	30,00 %	-	430,00 g/litre
VOC (volatile carbon)	25,29 %	-	361,65 g/litre

## SECTION 10. Stability and reactivity

### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

### 10.2. Chemical stability

## SECTION 10. Stability and reactivity ... / >>

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

#### XYLENE (MIXTURE OF ISOMERS)

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

#### REACTION MASS OF ETHYLBENZENE AND XYLENE

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

### 10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

### 10.5. Incompatible materials

Information not available

### 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

## SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Metabolism, toxicokinetics, mechanism of action and other information

Information not available

#### Information on likely routes of exposure

##### XYLENE (MIXTURE OF ISOMERS)

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

##### REACTION MASS OF ETHYLBENZENE AND XYLENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

##### XYLENE (MIXTURE OF ISOMERS)

Toxic action on the central nervous system (encephalopathies); irritant action on the skin, conjunctiva, cornea and respiratory system.

##### REACTION MASS OF ETHYLBENZENE AND XYLENE

Toxic action on the central nervous system (encephalopathies); irritant action on the skin, conjunctiva, cornea and respiratory system.

#### Interactive effects

##### XYLENE (MIXTURE OF ISOMERS)

Alcohol intake interferes with the metabolism of the substance, inhibiting it. Consumption of ethanol (0.8 g / kg) before a 4 hour exposure to xylenes vapors (145 and 280 ppm) causes a 50% decrease in the excretion of metilippuric acid, while the blood concentration of xylenes rises about 1.5-2 times. At the same time, there is an increase in the secondary side effects of ethanol. The metabolism of xylenes is enhanced by phenobarbital and 3-methyl-colanthrene-type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with glycine, which results in a decrease in urinary excretion of metilippuric acid. Other industrial products can interfere with the metabolism of xylenes.



## SECTION 11. Toxicological information ... / >>

### REACTION MASS OF ETHYLBENZENE AND XYLENE

Alcohol intake interferes with the metabolism of the substance, inhibiting it. Consumption of ethanol (0.8 g / kg) before a 4 hour exposure to xylenes vapors (145 and 280 ppm) causes a 50% decrease in the excretion of metilippuric acid, while the blood concentration of xylenes rises about 1.5-2 times. At the same time, there is an increase in the secondary side effects of ethanol. The metabolism of xylenes is enhanced by phenobarbital and 3-methyl-colanthrene-type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with glycine, which results in a decrease in urinary excretion of metilippuric acid. Other industrial products can interfere with the metabolism of xylenes.

### ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture: > 20 mg/l  
ATE (Oral) of the mixture: Not classified (no significant component)  
ATE (Dermal) of the mixture: >2000 mg/kg

### XYLENE (MIXTURE OF ISOMERS)

LD50 (Dermal): > 5000 mg/kg Rabbit  
STA (Dermal): 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)  
LD50 (Oral): 5627 mg/kg Rat  
LC50 (Inhalation vapours): 6700 ppm/4h Rat

### REACTION MASS OF ETHYLBENZENE AND XYLENE

LD50 (Dermal): > 2000 mg/kg Rabbit  
STA (Dermal): 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)  
LD50 (Oral): > 3523 mg/kg Rat  
LC50 (Inhalation vapours): > 27,6 mg/l/4h Rat  
STA (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)

### HEPTANE

LD50 (Dermal): > 2920 mg/kg Rat  
LD50 (Oral): > 5840 mg/kg Rat  
LC50 (Inhalation vapours): > 23300 mg/l/4h Rat

### SKIN CORROSION / IRRITATION

Causes skin irritation

### SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

### RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

### CARCINOGENICITY

Does not meet the classification criteria for this hazard class

### XYLENE (MIXTURE OF ISOMERS)

Classified in group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC). The US Environmental Protection Agency (EPA) claims that "the data were found to be inadequate for an assessment of carcinogenic potential."

### REACTION MASS OF ETHYLBENZENE AND XYLENE

Classified in group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC). The US Environmental Protection Agency (EPA) claims that "the data were found to be inadequate for an assessment of carcinogenic potential."

### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

## SECTION 11. Toxicological information ... / >>

### STOT - SINGLE EXPOSURE

May cause respiratory irritation

### STOT - REPEATED EXPOSURE

May cause damage to organs

### ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class Viscosity: 28000

### 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

## SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

### 12.1. Toxicity

#### REACTION MASS OF ETHYLBENZENE AND XYLENE

LC50 - for Fish	2,6 mg/l/96h oncorhynchus mykiss
EC50 - for Algae / Aquatic Plants	2,2 mg/l/72h Chlorella vulgaris
Chronic NOEC for Fish	> 1,3 mg/l 56 d
Chronic NOEC for Crustacea	0,74 mg/l 7 d

#### HEPTANE

LC50 - for Fish	375 mg/l/96h Tilapia mossambica
EC50 - for Crustacea	82,5 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	1,5 mg/l/72h Algae
Chronic NOEC for Fish	1,534 mg/l Fish 28 d
Chronic NOEC for Crustacea	1 mg/l Dafnia- Dafnia magna 21 d

### 12.2. Persistence and degradability

#### XYLENE (MIXTURE OF ISOMERS)

Solubility in water	100 - 1000 mg/l
Rapidly degradable	

#### REACTION MASS OF ETHYLBENZENE AND XYLENE

Solubility in water	60 mg/l
Rapidly degradable	

#### HEPTANE

Solubility in water	0,1 - 100 mg/l
Rapidly degradable	

### 12.3. Bioaccumulative potential

#### XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: n-octanol/water	3,12
BCF	25,9

#### REACTION MASS OF ETHYLBENZENE AND XYLENE

Partition coefficient: n-octanol/water	3,16
BCF	29

#### HEPTANE

Partition coefficient: n-octanol/water	4,5
BCF	552

### 12.4. Mobility in soil

## SECTION 12. Ecological information ... / >>

XYLENE (MIXTURE OF ISOMERS) Partition coefficient: soil/water	2,73
REACTION MASS OF ETHYLBENZENE AND XYLENE Partition coefficient: soil/water	2,73 mg/l
HEPTANE Partition coefficient: soil/water	2,38

### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

### 12.7. Other adverse effects

Information not available

## SECTION 13. Disposal considerations

### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## SECTION 14. Transport information

### 14.1. UN number or ID number

ADR / RID, IMDG, IATA: 1263

### 14.2. UN proper shipping name

ADR / RID: PAINT or PAINT RELATED MATERIAL  
IMDG: PAINT or PAINT RELATED MATERIAL  
IATA: PAINT or PAINT RELATED MATERIAL

### 14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



### 14.4. Packing group

ADR / RID, IMDG, IATA: II

The product, if packed in packages of less than 450 litres, can be assigned to P.G. III as provided for by 2.2.3.1.4 of the ADR.

The product, if packed in packages of less than 450 litres, can be assigned to P.G. III as provided for by 2.3.2.2 of the IMDG Code.

The product, if packed in packages of less than 30 litres, can be assigned to P.G. III as provided for by 3.3.3.1.1 of the DGR IATA.

## SECTION 14. Transport information ... / >>

### 14.5. Environmental hazards

ADR / RID: Environmentally Hazardous



IMDG: Marine Pollutant



IATA: NO

For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

### 14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 33	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
	Special provision: 640D		
IMDG:	EMS: F-E, S-E	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 60 L	Packaging instructions: 364
	Passengers:	Maximum quantity: 5 L	Packaging instructions: 353
	Special provision:	A3, A72, A192	

### 14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

## SECTION 15. Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

<u>Product</u>	
Point	3 - 40
<u>Contained substance</u>	
Point	75
Point	52
	isononyl phthalate
	REACH Reg.: 01-2119430798-28

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors  
not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC):

Special finishes.

### 15.2. Chemical safety assessment

## SECTION 15. Regulatory information ... / >>

A chemical safety assessment has been performed for the following contained substances  
XYLENE (MIXTURE OF ISOMERS)  
REACTION MASS OF ETHYLBENZENE AND XYLENE  
HEPTANE

## SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Liq. 2</b>	Flammable liquid, category 2
<b>Flam. Liq. 3</b>	Flammable liquid, category 3
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>STOT RE 2</b>	Specific target organ toxicity - repeated exposure, category 2
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>Aquatic Chronic 2</b>	Hazardous to the aquatic environment, chronic toxicity, category 2
<b>Aquatic Chronic 3</b>	Hazardous to the aquatic environment, chronic toxicity, category 3
<b>H225</b>	Highly flammable liquid and vapour.
<b>H226</b>	Flammable liquid and vapour.
<b>H312</b>	Harmful in contact with skin.
<b>H332</b>	Harmful if inhaled.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H373</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H336</b>	May cause drowsiness or dizziness.
<b>H411</b>	Toxic to aquatic life with long lasting effects.
<b>H412</b>	Harmful to aquatic life with long lasting effects.

### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

### GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament

## SECTION 16. Other information ... / >>

5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website

### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

### CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

### Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 08 / 09 / 10 / 11 / 12 / 15 / 16.