Printing date: 24.11.2023 Version: 34 (replaces version 33) Revision: 24.11.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: SOLL Body Cavity Protection, Transparent

· Article number: S700315 · UFI: FE3G-X0F7-P00F-J0N1

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against -
- · Application of the substance / the mixture Surface protection
- · 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

UAB HELVINA

Parko str. 96, Ramu iai

LT-54464 Kaunas distr., Lithuania

Tel: +370 37 308901 Fax: +370 37 308902 E-mail: info@helvina.lt

· 1.4 Emergency telephone number:

Poison control and information office: Tel.: +370 5 236 2052 or +370 687 53378

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

02 GHS07

- · Signal word Warning
- $\cdot \ Hazard\text{-}determining \ components \ of \ labelling:$

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hydrocarbons,C9, aromatics

Hazard statements

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Printing date: 24.11.2023 Version: 34 (replaces version 33) Revision: 24.11.2023

Trade name: SOLL Body Cavity Protection, Transparent

(Contd. of page 1)

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.
P280 Wear protective gloves / eye protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description:

Mixture of waxes, additives, solvents

| · Dangerous components: | | |
|---|---|----------|
| EC number: 919-857-5 Reg.nr.: 01-2119463258-33 | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | 25-<50% |
| | Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336, EUH066 | |
| CAS: 128601-23-0 EC number: 918-668-5 Reg.nr.: 01-2119455851-35 | Hydrocarbons,C9,aromatics Consisting of: 98-82-8 isopropylbenzene (<2%); 71-43-2 benzene (<0,1%) Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066 | 2,5-<10% |
| EC number: 918-481-9 Reg.nr.: 01-2119457273-39 | Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclic, <2% | 2,5-<10% |
| CAS: 1305-62-0 EINECS: 215-137-3 Reg.nr.: 01-2119475151-45 | Calcium dihydroxide Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335 | 1-<2,5% |

• Additional information: The text of the hazard statements mentioned here can be found in chapter 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)

Printing date: 24.11.2023 Version: 34 (replaces version 33) Revision: 24.11.2023

Trade name: SOLL Body Cavity Protection, Transparent

(Contd. of page 2)

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Water haze

Fire-extinguishing powder

Carbon dioxide

Alcohol resistant foam

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

DE-EN

(Contd. on page 4)

Printing date: 24.11.2023 Version: 34 (replaces version 33) Revision: 24.11.2023

Trade name: SOLL Body Cavity Protection, Transparent

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

| Ingredients with limit values that require monitoring at the workplace: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclic, <2% aromatics. TLV (Germany) Short-term value: 1200, 184 57-11-4 stearic acid, pure MAK (Germany) vgl.Abschn.IIb und Xc 9003-29-6 Polybutene (Isobutylene/butene coplymer) MAK (Germany) vgl. Abschn. IIb und Xc DNELs Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics |
|--|
| TLV (Germany) Short-term value: 1200, 184 57-11-4 stearic acid, pure MAK (Germany) vgl.Abschn.IIb und Xc 9003-29-6 Polybutene (Isobutylene/butene coplymer) MAK (Germany) vgl. Abschn. IIb und Xc DNELs |
| 57-11-4 stearic acid, pure MAK (Germany) vgl.Abschn.IIb und Xc 9003-29-6 Polybutene (Isobutylene/butene coplymer) MAK (Germany) vgl. Abschn. IIb und Xc DNELs |
| MAK (Germany) vgl.Abschn.IIb und Xc 9003-29-6 Polybutene (Isobutylene/butene coplymer) MAK (Germany) vgl. Abschn. IIb und Xc DNELs |
| 9003-29-6 Polybutene (Isobutylene/butene coplymer) MAK (Germany) vgl. Abschn. IIb und Xc • DNELs |
| MAK (Germany) vgl. Abschn. IIb und Xc • DNELs |
| · DNELs |
| |
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics |
| if di bell bons, es ell, il dimines, isourmines, es elles, '270 di bindeles |
| Oral DNEL Long term-systemic 125 mg/kg bw/day (Consumer) |
| Dermal DNEL Long term-systemic 125 mg/kg bw/day (Consumer) |
| 208 mg/kg bw/day (Worker) |
| Inhalative DNEL Long term-systemic 185 mg/m3 (Consumer) |
| 871 mg/m3 (Worker) |
| 128601-23-0 Hydrocarbons,C9,aromatics |
| Oral DNEL Long term-systemic 11 mg/kg bw/day (Consumer) |
| Dermal DNEL Long term-systemic 11 mg/kg bw/day (Consumer) |
| 25 mg/kg bw/day (Worker) |
| Inhalative DNEL Long term-systemic 32 mg/m3 (Consumer) |
| 100 mg/m3 (Worker) |
| 1305-62-0 Calcium dihydroxide |
| Inhalative DNEL Acute-local 4 mg/m3 (Consumer) |
| 4 mg/m3 (Worker) |

1 mg/m3 (Consumer) 1 mg/m3 (Worker)

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

DNEL Long term-local

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

General ventilation

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation. Filter A2/P2

· Hand protection



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Version: 34 (replaces version 33) Revision: 24.11.2023 Printing date: 24.11.2023

Trade name: SOLL Body Cavity Protection, Transparent

(Contd. of page 4)

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm

· Penetration time of glove material

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection

Safety glasses



Tightly sealed goggles

Body protection:

Use protective suit. (EN-13034/6)

Fully skin-covering anti-static, chemical- and oil-resistant clothing and safety shoes are recommended. (EN1149; EN340&EN ISO 13688; EN13034-6).

• Environmental exposure controls Use an appropriate container to avoid environmental pollution.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state

· Colour: According to product specification

· Odour: Characteristic · Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range

· Flammability

· Lower and upper explosion limit

0,6 Vol % (64742-48-9 Hydrocarbons, C9-C11, n-· Lower:

alkanes, isoalkanes, cyclics, <2% aromatics)

7,5 Vol % (128601-23-0 Hydrocarbons, C9, aromatics) · Upper:

38 °C (128601-23-0 Hydrocarbons, C9, aromatics) · Flash point:

165-181 °C (128601-23-0

Flammable.

Hydrocarbons, C9, aromatics)

Mixture is non-polar/aprotic.

233 °C (Hydrocarbons, C10-C13, n-alkanes, · Ignition Temperature

isoalkanes, cyclic, <2% aromatics.)

· Decomposition temperature: Not determined.

· pH

· Viscosity:

· Kinematic viscosity at 20 °C 32 s (DIN 53211/4) · Kinematic viscosity at 40 °C $>20,5 \text{ mm}^2/\text{s}$

· Dynamic: Not determined ·Solubility

Not miscible or difficult to mix. · water:

· Partition coefficient n-octanol/water (log value) Not determined. 2,7 hPa (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, · Vapour pressure at 20 °C:

cyclics, <2% aromatics)

(Contd. on page 6)

DE-EN

Version: 34 (replaces version 33) Revision: 24.11.2023 Printing date: 24.11.2023

Trade name: SOLL Body Cavity Protection, Transparent

(Contd. of page 5)

· Density and/or relative density

Density at 20 °C: 0,813-0,834 g/cm³ Relative density Not determined. · Vapour density Not determined.

· 9.2 Other information

· Form: Fluid · Important information on protection of health and

environment, and on safety.

Product is not selfigniting. · Ignition temperature:

· Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

60,1 % · Organic solvents: 41,0 % · Solids content:

Not determined. · Evaporation rate

· Information with regard to physical hazard classes

Void · Explosives · Flammable gases Void Void · Aerosols Void · Oxidising gases Void · Gases under pressure

Flammable liquid and vapour. · Flammable liquids

Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids · Self-heating substances and mixtures Void

· Substances and mixtures, which emit flammable

gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | | |
|---|-----------|---|
| Oral | LD50 | >5000 mg/kg (Rat) (Acute Oral Toxicity) |
| Dermal | LD50 | 3160 mg/kg (Rabbit) (Acute Dermal Toxicity) |
| Inhalative | LC50 (4h) | >4951 mg/l (Rat) |

(Contd. on page 7)

Printing date: 24.11.2023 Version: 34 (replaces version 33) Revision: 24.11.2023

Trade name: SOLL Body Cavity Protection, Transparent

| | | (Contd. of page 6) |
|--|-------------------------------|--|
| | LC50 (4h) | 4951 mg/m3 (Rat) |
| 128601-23-0 Hydrocarbons,C9,aromatics | | |
| Oral | LD50 | 3492 mg/kg (Rat) |
| Dermal | LD50 | >3160 mg/kg (Rabbit) |
| Inhalative | LC50 (4h) | >6193 mg/l (Rat) (Acute Inhalation Toxicity) |
| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclic, <2% aromatics. | | |
| Oral | LD50 | >5000 mg/kg (Rat) |
| Dermal | LD50 | >2000 mg/kg (Rabbit) |
| Inhalative | LC50 (4h) | 4951 mg/l (Rat) |
| 1305-62-0 | 1305-62-0 Calcium dihydroxide | |
| Oral | LD50 | >2001 mg/kg (Rat) |
| | | >2500 mg/kg (Rabbit) |

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

| · Aquatic toxici | Aquatic toxicity: | |
|--|---|--|
| Hydrocarbon | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | |
| EL0 (48h) | 1000 mg/l (Daphnia magna) | |
| NOELR (72h) | 100 mg/l (Pseudokirchneriella subcapitata) | |
| EL50 (72h) | >1000 mg/l (Pseudokirchneriella subcapitata) | |
| LL50 (96h) | >1000 mg/l (Onc) | |
| 128601-23-0 Hydrocarbons,C9,aromatics | | |
| NOELR (72h) | 1 mg/l (Pseudokirchneriella subcapitata) | |
| EL50 (48h) | 3,2 mg/l (Daphnia magna) | |
| LL50 (96h) | 9,2 mg/l (Oncorhynchus mykiss) | |
| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclic, <2% aromatics. | | |
| EL0 (48h) | 1000 mg/l (Daphnia magna) | |
| EL0 (72h) | 1000 mg/l (Pseudokirchneriella subcapitata) | |
| LL0 (96h) | 1000 mg/l (Oncorhynchus mykiss) | |
| 1305-62-0 Cal | 1305-62-0 Calcium dihydroxide | |
| EC50 (72h) | 184,57 mg/l (Invertebrate) | |
| LC50 (96h) | 50,6 mg/l (Fish) | |
| EC50 | 59,1 mg/l (Daphnia magna) | |
| . 12.2 Parsistance and degradability Not easily biodegradable | | |

- 12.2 Persistence and degradability Not easily biodegradable
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.

(Contd. on page 8)

Printing date: 24.11.2023 Version: 34 (replaces version 33) Revision: 24.11.2023

Trade name: SOLL Body Cavity Protection, Transparent

(Contd. of page 7)

- · 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- · **vPvB**: Not applicable.
- 12.6 Endocrine disrupting properties

 The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- ·Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

| · European waste catalogue | |
|----------------------------|---|
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances |
| HP3 | Flammable |
| HP5 | Specific Target Organ Toxicity (STOT)/Aspiration Toxicity |
| HP14 | Ecotoxic |

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

| SECTION 14: | Transport | information |
|-------------|-----------|-------------|
|-------------|-----------|-------------|

| · 14.1 UN number or ID number · ADR, ADN, IMDG, IATA | UN1139 |
|--|--|
| · 14.2 UN proper shipping name · ADR, ADN · IMDG · IATA | UN1139 COATING SOLUTION COATING SOLUTION COATING SOLUTION, mixture |
| · 14.3 Transport hazard class(es) | |

· ADR, IMDG, IATA

· 14.6 Special precautions for user



| · Class · Label | 3 Flammable liquids. |
|--|----------------------|
| · ADN · ADN/R Class: | 3 Flammable liquids. |
| · 14.4 Packing group · ADR, IMDG, IATA | III |
| · 14.5 Environmental hazards: · Marine pollutant: | Yes |

Warning: Flammable liquids.

(Contd. on page 9)

Printing date: 24.11.2023 Version: 34 (replaces version 33) Revision: 24.11.2023

Trade name: SOLL Body Cavity Protection, Transparent

| | (Contd. of page |
|---|---|
| Hazard identification number (Kemler code): | 30 |
| EMS Number: | F-E,S-E |
| Stowage Category | Α |
| 14.7 Maritime transport in bulk according to IM | 10 |
| instruments | Not applicable. |
| Transport/Additional information: | |
| ADR | |
| Excepted quantities (EQ) | Code: E1 |
| | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 1000 ml |
| Transport category | 3 |
| Tunnel restriction code | D/E |
| IMDG | |
| Limited quantities (LQ) | 5L |
| Excepted quantities (EQ) | Code: E1 |
| • | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 1000 ml |
| UN "Model Regulation": | UN 1139 COATING SOLUTION, 3, III |

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- \cdot Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- · National regulations:
- · Technical instructions (air):

| Class | Share in % |
|-------|------------|
| NK | 50-<75 |

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · VOC-CH 60,11 %

(Contd. on page 10)

Printing date: 24.11.2023 Version: 34 (replaces version 33) Revision: 24.11.2023

Trade name: SOLL Body Cavity Protection, Transparent

(Contd. of page 9)

- · VOC-EU 488,7-501,3 g/l
- · Danish MAL Code 5-4
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008

Physical and chemical properties: The classification is based on the results of the mixtures tested. Health hazards, Environmental hazards: The method of classification of mixtures based on the constituents of the mixture (sum formula).

Department issuing SDS:

Produktsicherheit

Research & Development

- · Contact: info@helvina.lt
- Date of previous version: 21.11.2023
- · Version number of previous version: 33

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3