Revision nr. 2 SAFETY DATA SHEET Dated 13/02/2023 Printed on 16/02/2023 Nitro Thinner SOLL NITRO 646 Page n. 1/18 Replaced revision:1 (Dated: 07/04/2021) Safety Data Sheet According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH SECTION 1. Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier STN1 010M Code: Product name Nitro Thinner SOLL 646 (in metal container) UFI: Q7NJ-K02N-U00R-TDK8 1.2. Relevant identified uses of the substance or mixture and uses advised against Intended use For washing painting tools 1.3. Details of the supplier of the safety data sheet Name **UAB HELVINA** Full address Parko str. 96, Ramuciai **District and Country** LT-54464 Kaunas district Lithuania Tel. +370 308901 Fax. +370 308902 e-mail address of the competent person responsible for the Safety Data Sheet info@helvina.lt 1.4. Emergency telephone number For urgent inquiries refer to Poison control and information office: Tel.: +370 5 236 2052 or +370 687 53378

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:
Flammable liquid, category 2

H225

Highly flammable liquid and vapour.

Nitro Thinner SOLL NITRO 646

Revision nr. 2

Dated 13/02/2023 Printed on 16/02/2023

Page n. 2/18

Replaced revision:1 (Dated: 07/04/2021)

Reproductive toxicity, category 2	H361d
Acute toxicity, category 4	H302
Aspiration hazard, category 1	H304
Specific target organ toxicity - repeated exposure, category 2	H373
Eye irritation, category 2 Skin irritation, category 2 Specific target organ toxicity - single exposure, category 3 Specific target organ toxicity - single exposure, category 2 Hazardous to the aquatic environment, chronic toxicity, category 3	H319 H315 H336 H371 H412

Suspected of damaging the unborn child. Harmful if swallowed. May be fatal if swallowed and enters airways. May cause damage to organs through prolonged or repeated exposure. Causes serious eye irritation. Causes skin irritation. May cause drowsiness or dizziness. May cause damage to organs. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.



Precautionary statements:

P210 P331 P280 P301+P310 P370+P378 P261 P101 P102 P501	 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do NOT induce vomiting. Wear protective gloves/ protective clothing / eye protection / face protection. IF SWALLOWED: immediately call a POISON CENTER / doctor. In case of fire: use chemical powder to extinguish. Avoid breathing vapours. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Dispose of contents/container in accordance with the instructions of the locals / regionals / nationals / internationals administrations.
Contains:	Toulene METHYL ACETATE METHANOL

2.3. Other hazards

Nitro Thinner SOLL NITRO 646

Revision nr. 2 Dated 13/02/2023 Printed on 16/02/2023 Page n. 3/18

Replaced revision:1 (Dated: 07/04/2021)

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
Toulene		
INDEX 601-021-00-3	58 ≤ x < 66	Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 3 H412
EC 203-625-9		
CAS 108-88-3		
REACH Reg. 01-2119471310-51- xxxx		
METHYL ACETATE		
INDEX 607-021-00-X	$30 \le x < 35$	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
EC 201-185-2		
CAS 79-20-9		
REACH Reg. 01-2119459211-47- xxxx		
METHANOL		
INDEX 603-001-00-X	8≤x< 9	Flam. Liq. 2 H225, Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, STOT SE 1 H370
EC 200-659-6		STOT SE 2 H371: ≥ 3%
CAS 67-56-1		STA Oral: 100 mg/kg, STA Dermal: 300 mg/kg, STA Inhalation vapours: 3 mg/l
REACH Reg. 01-2119433307-44- xxxx		~

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Nitro Thinner SOLL NITRO 646

Revision nr. 2

Dated 13/02/2023

Printed on 16/02/2023 Page n. 4/18

Replaced revision:1 (Dated: 07/04/2021)

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak. UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

Nitro Thinner SOLL NITRO 646

Revision nr. 2

Dated 13/02/2023 Printed on 16/02/2023

Page n. 5/18

Replaced revision:1 (Dated: 07/04/2021)

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

BGR	България		НАРЕДБА № 13 ОТ 30 ДЕ СВЪРЗАНИ С ЕКСПОЗИL 2020г.)	КЕМВРИ 2003 Г. ЗА ЗАЩИТА Н ИЯ НА ХИМИЧНИ АГЕНТИ ПРІ	А РАБОТЕЩИТЕ ОТ РИСКОВЕ, 1 РАБОТА (изм. ДВ. бр.5 от 17 Януари
DEU	Deutschland		Technischen Regeln für Ge MAK- und BAT-Werte-Liste Arbeitsstoffe Mitteilung 56	fahrstoffe (TRGS 900) - Liste der 2020, Ständige Senatskommissio	Arbeitsplatzgrenzwerte und Kurzzeitwerte. on zur Prüfung gesundheitsschädlicher
ESP	Esnaña		l ímites de exposición profe	sional para agentes químicos en	Esnaña 2021
FRA	France		Valeurs limites d'exposition	professionnelle aux agents chimi	nues en France ED 984 - INRS
GRC	Ελλάδα		Π.Δ. 26/2020 (ΦΕΚ 50/Α΄ 6 2017/2398/ΕΕ, 2019/130/ΕΙ την προστασία των εργαζομ μεταλλαξινόγους παράγοντ:	3.2020) Εναρμόνιση της ελληνική Ε και 2019/983/ΕΕ «για την τροπα ιένων από τους κινδύνους που σι ες κατά την εργασία``»	ις νομοθεσίας προς τις διατάξεις των οδηγιών ποίηση της οδηγίας 2004/37/ΕΚ ``σχετικά με ινδέονται με την έκθεση σε καρκινογόνους ή
HRV	Hrvatska		Pravilnik o izmjenama i dop graničnim vrijednostima izlo	unama Pravilnika o zaštiti radnika ženosti i biološkim graničnim vrije	od izloženosti opasnimkemikalijama na radu, dnostima (NN 1/2021)
ITA	Italia		Decreto Legislativo 9 Aprile	2008, n.81	
LTU	Lietuva		Jsakymas dėl lietuvos higie Matavimo ir poveikio vertini patvirtinimo	nos normos hn 23:2011 "cheminiu mo bendrieji reikalavimai"	į medžiagų profesinio poveikio ribiniai dydžiai.
LVA	Latvija		Grozījumi Ministru kabineta saskarē ar kīmiskajām vielā	2007. gada 15. maija noteikumos m darba vietās" (prot. Nr. 32 18. š	ν Νr. 325 "Darba aizsardzības prasības §; prot. Nr. 1 22. §)
POL	Polska		Rozporządzenie ministra ro w sprawie najwyższych dop środowisku pracy	zwoju, pracy i technologii z dnia uszczalnych stężeń i natężeń czy	18 lutego 2021 r. Zmieniające rozporządzenie nników szkodliwych dla zdrowia w
ROU	România		Hotărârea nr. 53/2021 pentr si completarea hotărârii guy	u modificarea hotărârii guvernulu ernului nr. 1.093/2006	i nr. 1.218/2006, precum și pentru modificarea
SVN	Slovenija		Pravilnik o varovanju delavo RS, št. 100/01, 39/05, 53/07 ZVZD-1, 38/15, 78/18 in 78	ev pred tveganji zaradi izpostavlj 7, 102/10, 43/11 – /19)	enosti kemičnim snovem pri delu (Uradni list
TUR	Türkiye		Kimyasal Maddelerle Çalışı	nalarda Sağlık ve Güvenlik Önlen	nleri Hakkında Yönetmelik 12.08.2013 / 28733
GBR	United Kingdom		EH40/2005 Workplace expo	osure limits (Fourth Edition 2020)	
EU	OELEU		Directive (EU) 2022/431; Di	rective (EU) 2019/1831; Directive	(EU) 2019/130; Directive (EU) 2019/983; 2009/161/EU: Directive 2006/15/EC: Directive
			2004/37/EC: Directive 2000	/39/EC: Directive 98/24/EC: Direc	tive 91/322/FFC
	TLV-ACGIH		ACGIH 2021		
Toulene					
Threshold L	imit Value				
Type		Country	TWA/8h	STEL/15min	Remarks /
.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		000		0.22.000	Observations

Nitro Thinner SOLL NITRO 646

Revision nr. 2 Dated 13/02/2023

Printed on 16/02/2023 Page n. 6/18 Replaced revision:1 (Dated: 07/04/2021)

		ma/m3	maa	ma/m3	maa			
TLV	BGR	192	50	384	100	SKIN		
AGW	DEU	190	50	760	200	SKIN		
MAK	DEU	190	50	760	200	SKIN		
VLA	ESP	192	50	384	100	SKIN		
VLEP	FRA	76,8	20	384	100	SKIN		
TLV	GRC	192	50	384	100			
GVI/KGVI	HRV	192	50	384	100	SKIN		
VLEP	ITA	192	50			SKIN		
RD	LTU	192	50	384	100	SKIN		
RV	LVA	50	14	150	40	SKIN		
NDS/NDSCh	POL	100		200		SKIN		
TLV	ROU	192	50	384	100	SKIN		
MV	SVN	192	50	384	100	SKIN		
ESD	TUR	192	50	384	100	SKIN		
WEL	GBR	191	50	384	100	SKIN		
OEL	EU	192	50	384	100	SKIN		
TLV-ACGIH			20					
Predicted no-effect concentration	- PNEC							
Normal value in fresh water				0,074	mg	/I		
Normal value in marine water				0,0074	mg	/I		
Normal value for fresh water sediment				1,78	mg	/I		
Normal value for marine water se	diment			0,178	mg	/I		
Normal value for water, intermitte	nt release			0,00378	mg	/I		
Normal value of STP microorgani	sms			0,84	mg	/I		
Normal value for the terrestrial co	mpartment			0,313	mg	/kg		
Health - Derived no-effect le	evel - DNEL / D Effects on	MEL			Effects on			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic
Oral				systemic 8,13 mg/kg/d		systemic		systemic
Inhalation	226 mg/m3	226 mg/m3	56,5 mg/m3	56,5 mg/m3	384 mg/m3	384 mg/m3	192 mg/m3	192 mg/m3
Skin				226 mg/kg/d			VND	384 mg/kg/d
METHYL ACETATE Threshold Limit Value								
Туре	Country	TWA/8h		STEL/15min		Remarks /	ne	
		mg/m3	ppm	mg/m3	ppm	Observatio	/15	
AGW	DEU	620	200	1240 (C)	400 (C)			
МАК	DEU	310	100	1240	400			
VLA	ESP	616	200	770	250			
VLEP	FRA	610	200	760	250	SKIN		
TLV	GRC	610	200	760	250			
GVI/KGVI	HRV	616	200	770	250			

Nitro Thinner SOLL NITRO 646

Revision nr. 2

Dated 13/02/2023

Printed on 16/02/2023 Page n. 7/18 Replaced revision:1 (Dated: 07/04/2021)

RD	1 TI I	450	150	900	300			
RV		100	150	300	500			
	POL	250		600				
	ROLL	200	63	600	188			
	SVN	610	200	1240	400			
WEI	GBR	616	200	770	250			
	GBR	606	200	757	250			
Predicted no offect concentration	DNEC	000	200	151	230			
Normal value in fresh water	- FNEC			0.12		<i>n</i>		
Normal value for freeh water				0,12	mg/	1		
Normal value for fresh water sedir	nent			0,12	riig/	к <u>у</u>		
Normal value of STP microorganis	sms			100	mg/	a		
Normal value for the terrestrial cor				0,042	mg/	кg		
Health - Derived no-effect le	Effects on	1EL			Effects on			
Route of exposure	consumers Acute local	Acute systemic	Chronic local	Chronic	workers Acute local	Acute	Chronic local	Chronic
				systemic		systemic		systemic
Inhalation	VND	VND	VND	VND	260 ma/m3	260 mg/m3	260 ma/m3	610 mg/m3
Skin	VND	VND	VND	VND	VND	40 mg/kg /d	VND	40 mg/kg/d
METHANOL								
Threshold Limit Value								
Туре	Country	TWA/8h		STEL/15min		Remarks / Observatio	ns	
		mg/m3	ppm	mg/m3	ppm	0000114110	10	
TLV	BGR	260	200			SKIN		
AGW	DEU	270	200	1080	800	SKIN		
МАК	DEU	130	100	260	200	SKIN		
VLA	ESP	266	200			SKIN		
VLEP	FRA	260	200	1300	1000	SKIN	11	
	GRC	260	200	325	250	01/11		
GVI/KGVI	HRV	260	200			SKIN		
VLEP		260	200			SKIN		
RD	LIU	260	200			SKIN		
RV	LVA	260	200			SKIN		
NDS/NDSCh	POL	100		300		SKIN		
TLV	ROU	260	200			SKIN		
MV	SVN	260	200	1040	800	SKIN		
ESD	TUR	260	200			SKIN		
WEL	GBR	266	200	333	250	SKIN		
OEL	EU	260	200					
TLV-ACGIH		262	200	328	250	SKIN		
Predicted no-effect concentration	- PNEC							
Normal value in fresh water				150	mg/	1		
Normal value in marine water				15,4	mg/	1		
Normal value for fresh water sediment				570,4	mg/	/kg		
Normal value of STP microorganis	sms			100	mg/	1		

Nitro Thinner SOLL NITRO 646

Revision nr. 2

Dated 13/02/2023

Printed on 16/02/2023 Page n. 8/18

Replaced revision:1 (Dated: 07/04/2021)

L								
Normal value for the terrestrial	compartment			23,5	mg	/kg		
Health - Derived no-effect	Effects on	MEL			Effects on			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic
Oral	VND	8 mg/kg/d	VND	8 mg/kg/d		Systemic		systemic
Inhalation	50 mg/mc	VND	50 mg/mc	VND	260 ma/mc	VND	260 mg/mc	VND
Skin	VND	8 mg/kg/d	VND	8 mg/kg/d	VND	40 mg/kg/d	VND	40 mg/kg/d
Legend:								
(C) = CEILING ; INHAL = I	nhalable Fraction	; RESP = Res	pirable Fraction	n ; THORA =	= Thoracic Frac	tion.		
VND = hazard identified but r medium hazard ; HIGH = h	no DNEL/PNEC a nigh hazard.	vailable ; NEA	= no exposure	expected ;	NPI = no hazar	d identified ;	LOW = low ha	azard ; MED =
Toulene								
Components with biological li 108-88-3 Toluene IBE (Italy): 0.02 mg / I Matrix: blood Time of withdrawal: first shift Biological indicator of exposu 0.03 mg / I Matrix: urine Time of withdrawal: at the en Biological indicator of exposu 0.03 mg / g creatinine Matrix: urine Time of withdrawal: at the en Biological indicator of exposu 8.2. Exposure controls	mit values: last working weel re: toluene d of the shift re: toluene d of the shift re: o-cresol	ĸ						
As the use of adequate tech through effective local aspira When choosing personal pro Personal protective equipment	nical equipment tion. tective equipment nt must be CE ma	must always take t, ask your chemic arked, showing tha	e priority over p cal substance s at it complies w	bersonal protec supplier for adv vith applicable s	ctive equipmen rice. standards.	t, make sure t	that the workpla	ace is well aired
Provide an emergency showe	er with face and e	eye wash station.						
Exposure levels must be kep maximum protection (e.g. rec	t as low as possi luction in replace	ble to avoid signif ment times).	icant build-up i	n the organism	n. Manage pers	onal protective	e equipment so	as to guarantee
HAND PROTECTION Protect your hands with work with a chemical protection ind the case, refer to the UNI EN	gloves of catego dex of at least 5 (standard 374. G	ory III (see standa permeation> of 2- loves must be per	rd EN 374). Pr 40 minutes). U iodically inspec	otect your han se gloves acco cted and replac	ds with work gl ording to the con ced in case of w	oves made of nditions and lin vear, perforation	suitable materia mits set by the on or contamina	al: nitrile or PVC manufacturer. In tion (1174).
SKIN PROTECTION Wear category II professiona and water after removing pro	I long-sleeved ov tective clothing.	veralls and safety	footwear (see	Regulation 20	16/425 and sta	ndard EN ISC) 20344). Wash	body with soap

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

Nitro Thinner SOLL NITRO 646

Revision nr. 2

Dated 13/02/2023

Printed on 16/02/2023 Page n. 9/18

Replaced revision:1 (Dated: 07/04/2021)

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	colourless	
Odour	characteristic of solvent	
Melting point / freezing point Initial boiling point Boiling range	-95 ℃ 54 ℃ 54-110,6 ℃	Substance:Toulene Substance:METHYL ACETATE Remark: METHYL ACETATE - TOLUENE
Flammability	Flammable liquid and vapour	
Lower explosive limit Upper explosive limit Flash point Auto-ignition temperature	1,1 % (∨/∨) 7,1 % (∨/∨) -14 °C 460 °C	Substance:Toulene Substance:Toulene Substance:METHYL ACETATE
Decomposition temperature	not available	
рН	not available	
Kinematic viscosity	not available	
Solubility	soluble in organic solvents	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	350 hPa	Substance:METHYL ACETATE Temperature: 20 °C
Density and/or relative density Relative vapour density	0,882 not available	Method:INTERNO
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Nitro Thinner SOLL NITRO 646

Revision nr. 2

Dated 13/02/2023

Printed on 16/02/2023 Page n. 10/18

Replaced revision:1 (Dated: 07/04/2021)

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EC)

VOC (volatile carbon)

100,00 % - 882,00 g/litre 73,11 % - 644,87 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

Toulene

Avoid exposure to: light.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

Toulene

Risk of explosion on contact with: fuming sulphuric acid,nitric acid,silver perchlorate,nitrogen dioxide,non-metal halogenates,acetic acid,organic nitrocompounds. May form explosive mixtures with: air. May react dangerously with: strong oxidising agents, strong acids, sulphur.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Nitro Thinner SOLL NITRO 646

Revision nr. 2

Dated 13/02/2023

Printed on 16/02/2023 Page n. 11/18 Replaced revision:1 (Dated: 07/04/2021)

Information not available

Information on likely routes of exposure

Toulene

WORKERS: inhalation; contact with the skin. POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

METHANOL

WORKERS: inhalation; contact with the skin. POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Toulene

Toxic effect on the central and peripheral nervous system with encephalopathy and polyneuritis; irritating for the skin, conjunctiva, cornea and respiratory apparatus.

METHANOL

The minimum lethal dose for humans by ingestion is considered to be in the range from 300 to 1000 mg/kg. Ingestion of 4-10 ml of the substance may cause permanent blindness in adult humans (IPCS).

Interactive effects

Toulene Certain drugs and other industrial products can interfere with the metabolism of the toluene.

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture: ATE (Oral) of the mixture: ATE (Dermal) of the mixture:

Toulene

LD50 (Dermal): LD50 (Oral): LC50 (Inhalation vapours): > 20 mg/l 1136,36 mg/kg >2000 mg/kg

12267 mg/kg Rabbit 5000 mg/kg Rat 25,7 mg/l/4h Rat

METHANOL

LD50 (Dermal): STA (Dermal):

LD50 (Oral):

17100 mg/kg (coniglio) 300 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

> 1187 mg/kg (ratto)

Nitro Thinner SOLL NITRO 646

Revision nr. 2

Dated 13/02/2023 Printed on 16/02/2023

Page n. 12/18

Replaced revision:1 (Dated: 07/04/2021)

STA (Oral):

LC50 (Inhalation vapours): STA (Inhalation vapours): (figure used for calculation of the acute toxicity estimate of the mixture) 128,2 mg/l (ratto) 3 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

100 mg/kg estimate from table 3.1.2 of Annex I of the CLP

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Toulene

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 1999). The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

REPRODUCTIVE TOXICITY

Suspected of damaging the unborn child

STOT - SINGLE EXPOSURE

May cause damage to organs

Nitro Thinner SOLL NITRO 646

Revision nr. 2 Dated 13/02/2023

Printed on 16/02/2023 Page n. 13/18 Replaced revision:1 (Dated: 07/04/2021)

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

May cause damage to organs

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment. 12.1. Toxicity

Information not available

12.2. Persistence and degradability

Toulene	
Solubility in water	100 - 1000 mg/l
Rapidly degradable METHANOL	
Solubility in water	1000 - 10000 mg/l
Rapidly degradable METHYL ACETATE	
Solubility in water	243500 mg/l
Rapidly degradable I2.3. Bioaccumulative potential	
Toulene	
Partition coefficient: n-octanol/water	2,73
BCF	90
METHANOL	
Partition coefficient: n-octanol/water	-0,77
BCF	0,2

METHYL ACETATE

Nitro Thinner SOLL NITRO 646

0,18

Revision nr. 2

Dated 13/02/2023

Printed on 16/02/2023 Page n. 14/18

Replaced revision:1 (Dated: 07/04/2021)

Partition coefficient: n-octanol/water

12.4. Mobility in soil

METHYL ACETATE Partition coefficient: soil/water

0,18

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA:	1263
- , -,	

14.2. UN proper shipping name

ADR / RID:	PAINT RELATED MATERIAL
IMDG:	PAINT RELATED MATERIAL
IATA:	PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR / RID:	Class: 3	Label: 3
IMDG:	Class: 3	Label: 3



		SAFETY DATA SH	EET	Revision nr. 2 Dated 13/02/2023
		Nitro Thinner SOLL NIT	RO 646	Printed on 16/02/2023
				Page n. 15/18 Replaced rovision:1 (Deted: 07/04/2021)
IATA:	Class: 3	Label: 3	*	
14.4. Packing gro	oup			
ADR / RID, IMD	G, IATA:	II		
14.5. Environmer	ntal hazards			
ADR / RID:	NO			
IMDG:	NO			
IATA:	NO			
14.6. Special pred	cautions for user			
ADR / RID:		HIN - Kemler: 33	Limited Quantities: 5	Tunnel restriction code: (D/F)
		Special provision: 640D	-	0000. (5, 2)
IMDG:		EMS: F-E, <u>S-E</u>	Limited Quantities: 5	
IATA:		Cargo:	L Maximum quantity: 60 L	Packaging instructions: 364
		Pass.:	Maximum quantity: 5 L	Packaging instructions: 353
		Special provision:	A3, A72, A192	
14.7. Maritime tra	insport in bulk acco	ording to IMO instruments		
Information not rel	evant			
SECTION 1	5. Regulatory	information		
15.1. Safety, he	alth and environme	ntal regulations/legislation specific f	for the substance or mixture	
Seveso Category	- Directive 2012/18/E	U: P5c		
Restrictions relatin	ng to the product or c	ontained substances pursuant to Annex	XVII to EC Regulation 1907/2006	
Product Point		3 - 40		
Contained substar	nce			
Point		75		

Point 69

METHANOL REACH Reg.: 01-2119433307-44-xxxx

Nitro Thinner SOLL NITRO 646

Revision nr. 2

Dated 13/02/2023

Printed on 16/02/2023 Page n. 16/18

Replaced revision:1 (Dated: 07/04/2021)

Point	48	Toulene REACH Reg.: 01- 2119471310-51-xxxx		
Regulation (EU) 2019/1148 - c	on the marketing and use	e of explosives precursors		
not applicable				
Substances in Candidate List	(Art. 59 REACH)			
On the basis of available data	, the product does not co	ontain any SVHC in percentage ≥ than 0,1%.		
Substances subject to authoris	sation (Annex XIV REAC	<u>2H)</u>		
None				
Substances subject to exporta	tion reporting pursuant to	o Regulation (EU) 649/2012:		
None				
Substances subject to the Rot	terdam Convention:			
None				
Substances subject to the Sto	ckholm Convention:			
None				
Healthcare controls				
Workers exposed to this cherr workers' health and safety are	nical agent must not unde modest and that the 98/	lergo health checks, provided that available risk /24/EC directive is respected.	<-assessment data prove that the risks	s related to the

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

This safety data sheet contains one or more Exposure Scenarios in an integrated form. Contents have been included in sections 1.2, 8, 9, 12, 15 and 16 of this safety data sheet.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Repr. 2	Reproductive toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
STOT SE 1	Specific target organ toxicity - single exposure, category 1
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2

Nitro Thinner SOLL NITRO 646

Revision nr. 2

Dated 13/02/2023 Printed on 16/02/2023

Page n. 17/18

Replaced revision:1 (Dated: 07/04/2021)

Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
STOT SE 2	Specific target organ toxicity - single exposure, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H361d	Suspected of damaging the unborn child.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H370	Causes damage to organs.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H371	May cause damage to organs.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008 DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament

Nitro Thinner SOLL NITRO 646

Revision nr. 2

Dated 13/02/2023

Printed on 16/02/2023 Page n. 18/18

Replaced revision:1 (Dated: 07/04/2021)

- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP) 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. 10th Edition Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

09.